
K-Ball®

Clip-on spray nozzles





SPRAY CHARACTERISTICS:

These nozzles simply clip over a pre-drilled pipe (9/16" dia. hole) and are available with a variety of spray balls, in various spray patterns, flow rates and spray angles.

CONSTRUCTION:

Made of corrosion-resistant plastic and stainless steel. Heavy-duty spring clip good to 100 p.s.i. at 175° F. A 316SS clip is also available, if required.

TYPICAL APPLICATIONS:


- Parts Cleaning
- Pretreatment
- Spray Washing & Rinsing

Double clip model also available.

DIMENSIONS

DIMENTOTOTO						
PIPE	Dim.	Dim.				
SIZE	Α	В				
1"	1 ³ / ₄ (45 mm)	2 ⁷ / ₈ (73 mm)				
11/4	2 (51 mm)	3 (77 mm)				
11/2	2 ¹ / ₈ (54 mm)	3 ¹ / ₈ (80 mm)				
2"	2 ³ / ₈ (61 mm)	3 ¹ / ₂ (89 mm)				

THE BEX "FINGER" SYSTEM



HOW TO ORDER COMPLETE K-BALL ASSEMBLIES

Use the correct body part number (from the parts listed in BOLD at the right), followed by the model number for the nozzle ball (see pages 65-67).

Example:

BF5070 nozzle balls are needed to fit onto a 1-1/4" pipe. Accurate alignment of the nozzles is critical, so the 1-1/4" body with "fingers" will be used. The correct PART number for this K-Ball nozzle assembly is 1.2KFBF5070.

K-BALL BODY COLORS AND PART NUMBERS

Pipe Sizes	1"	1-1/4"	1-1/2"	2"	
Standard Body	1K (white)	1.2K (grey)	1.5K (black)	2K (tan)	
Body with Fingers	1KF (green)	1.2KF (yellow)	1.5KF (red)	2KF (blue)	
Spring Clip	1KCL	1.2KCL	1.5KCL	2KCL	
O-ring	KOR	KOR	KOR	KOR	
K-Ball Cap	KCAP	KCAP	KCAP	KCAP	
SPRAY BALL: CHOOSE FROM THE TABLES ON PAGES 59 AND 60.					